



UNIDADES INTERIORES

RAV-RM561UTP-E  
RAV-RM801UTP-E  
RAV-RM1101UTP-E  
RAV-RM1401UTP-E



UNIDADES EXTERIORES

RAV-GP561ATP-E  
RAV-GP801ATP-E  
RAV-GP1101ATP-E  
RAV-GP1401ATP-E



CONTROLES REMOTOS

RBC-AX32U(W)-E  
TCB-AX32E2

RBC-AMS55E-ES(EN)  
RBC-ASC11E  
RBC-AMT32E  
RBC-AS41E



SCOP MÁX.



5,22

CAPACIDAD



5kW > 14kW

FUNCIONAMIENTO



-27°C > +52°C

DAYTONA CASSETTE R32 CARACTERÍSTICAS Monofásico & Trifásico

DIGITAL INVERTER

Nombre comercial	DAYTONA DI 56	DAYTONA DI 80	DAYTONA DI 110	DAYTONA DI 140
Unidad exterior	RAV-GM561ATP-E	RAV-GM801ATP-E	RAV-GM1101ATP-E	RAV-GM1401ATP-E
Unidad interior (Daytona Cassette)	RAV-RM561UTP-E	RAV-RM801UTP-E	RAV-RM1101UTP-E	RAV-RM1401UTP-E
<b>Capacidad de refrigeración</b>	<b>5</b>	<b>6,7</b>	<b>9,5</b>	<b>12</b>
Rango de refriger. (mín. - máx.)	1,5 - 5,6	1,5 - 8,0	3,0 - 11,2	3,0 - 13,2
Consumo (mín. - nom. - máx.)	0,26 - 1,56 - 1,86	0,26 - 2,22 - 2,60	0,60 - 2,87 - 4,10	0,60 - 4,29 - 4,71
EER	3,21	3,02	3,31	2,8
SEER	6,34	5,81	6,15	5,71
Clase de eficiencia energética	A++	A+	A++	A+
Consumo de electricidad estacional	285	404	597	783
<b>Capacidad de calefacción</b>	<b>5,6</b>	<b>7,7</b>	<b>11,2</b>	<b>12,8</b>
Rango de calefac. (mín. - máx.)	1,5 - 6,3	1,5 - 9,0	3,0 - 13,0	3,0 - 16,0
Consumo (mín. - nom. - máx.)	0,26 - 1,44 - 2,08	0,26 - 2,13 - 3,03	0,60 - 2,93 - 4,30	0,60 - 3,40 - 4,50
COP	3,90	3,62	3,82	3,76
SCOP	4,60	4,42	4,28	4,29
Clase de eficiencia energética	A+	A+	A+	A+
Consumo de electricidad estacional	1459	2349	2616	2672

DAYTONA CASSETTE R32 Datos físicos de la unidad interior

DIGITAL INVERTER

Unidad interior	RAV-RM561UTP-E	RAV-RM801UTP-E	RAV-RM1101UTP-E	RAV-RM1401UTP-E
Caudal de aire (A/B)	1050/780 - 291/217	1230/810 - 341/225	2010/1170 - 558/325	2100/1230 - 583/341
Nivel de presión sonora (A-M-B)	32-29-28	35-31-28	43-38-33	44-38-34
Dimensiones (Alt. x Anch. x Prof.)	256 x 840 x 840	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840
Peso	20	20	24	24
Dimensiones del panel (Alt.xAn.x Prof.)	30x950x950	30x950x950	30x950x950	30x950x950
Peso del panel	4,2	4,2	4,2	4,2

DAYTONA CASSETTE R32 Datos físicos de la unidad exterior

DIGITAL INVERTER

Unidad exterior	RAV-GM561ATP-E	RAV-GM801ATP-E	RAV-GM1101ATP-E	RAV-GM1401ATP-E
Caudal de aire	2400	2700	4080	4200
Nivel de presión sonora	46 / 48	48 / 52	54 / 57	55 / 57
Dimensiones (Alt. X Anc. X Prof.)	550 X 780 X290	550 X 780 X290	890 X 900 X 290	890 X 900 X 290
Peso	40	44	68	68
Máxima corriente en arranque (MCA)	15,5	15,5	22,8	22,8
Conexiones (gas/líquido)	1/2" - 1/4"	5/8" - 3/8"	5/8" - 3/8"	5/8" - 3/8"
Longitud mínima / máxima de tuberías	5 / 30	5 / 30	5 / 50	5 / 50
Diferencia máxima de altura	30	30	30	30
Longitud de tubería precargada	20	20	30	30
Carga adicional	20	35	35	35
Refrigerante	0,9	1,3	2,1	2,1

C: Modo de refrigeración H: Modo de calefacción